


*inspired by  
craftsmanship*

## ***Temac***

Tenoning machine for windows and door frames





forwards


backwards

Special program for tenon creation produces tear-free stormproofed sashes.




# Temac

Tenoning machine for windows and doors with a shaft for three tools



Horizontal milling unit for heritage sash horn detail (optional)




The creation of window components to be machined begins in **WinCreator** and is then sent to the machine. The machine settings for the components manufacturing are then automatically processed. The control system is also open to third-party software packages.



Electronic positioning of the tenoning unit

Tools with programmed positions and split working




NC control of the whole machine:  
cut-off saw, tenoning spindle, tenoning fence

**TECHNICAL DATA:**

- programmer with touch screen 10"
- cut-off saw  $\varnothing$  400 mm, motor 3 kW (4 HP)
- powered tenoning carriage
- fence with inclination +/- 45°
- tenoning unit L=330 mm, d=50 mm,
- motor 7,5 kW (10 HP), rpm 3000, max tool diameter 320 mm
- electronic control 320 mm

**Optional:**

- horizontal milling unit 4 kW (5 HP)



Technical data and description is subject of alteration. Pictures might show optional equipment that is not included in the standart machine specification.



---

**SOUKUP s.r.o.**  
Komerční 518, 251 02 Prague - Nupaky, Czech Republic  
Tel.: +420 241 403 110, E-mail: [info@soukup.cz](mailto:info@soukup.cz)  
[www.soukup.cz](http://www.soukup.cz)